MALCON MARINE AND LAND CONSTRUCTION

Slide-in coupling

SNPU



Description

Areas of use:

- To eliminate the accurate length cutting of ducts which the ordinary NPU connector sometimes requires when joining SR ducts. In this case the slide-in coupling shall be secured with screws or pop rivets.
- To make it possible to use a duct that is cut to a too short length – instead of having to cut a new duct to the correct length. In this case the slide-in coupling shall be secured with screws or pop rivets.
- To assist when joining two ducts which run towards each other. E.g. when building a system from two opposing directions. In this case the slide-in coupling shall be secured with screws or pop rivets.
- To assist when inserting or adding an other product into an existing system. E.g. the addition of a new piece of duct to replace a damaged part. In this case the slide-in coupling shall be secured with screws or pop rivets.
- To facilitate access when inspecting and/or cleaning a system – by simply sliding the coupling. The coupling acts as an access cap. Lindab do not recommend this use of larger dimensions than Ø315.

No Click function – has closed turned-over ends (at both ends).


Also available in other dimensions up to Ø400.

Order code

SNPU 160 150

Product
Dimension Ød$_1$
Nominal length L

Dimensions



Ød$_1$ nom	L nom	l$_i$ mm	m kg
80	150	133	0,18
80	300	284	0,32
80	500	548	0,69
100	150	133	0,22
100	300	284	0,40
100	500	548	0,84
125	150	133	0,28
125	300	284	0,50
125	500	548	1,07
160	150	133	0,36
160	300	284	0,65
160	500	548	1,38
180	150	133	0,40
180	300	284	0,72
180	500	548	1,53
200	150	133	0,56
200	300	293	1,02
200	500	548	1,76
224	150	133	0,62
224	300	293	1,13
224	500	548	1,95
250	150	177	0,91
250	300	297	1,35
250	500	527	2,17
315	150	177	1,18
315	300	297	1,72
315	500	527	2,76

We reserve the right to make changes without prior notice
rev. 2018-06-13

Lindab® www.lindabmarine.com